

# Epoca Compact

## Product Description



**ege**

THE URGE TO EXPLORE SPACE

| Product description                 | Methods                            | Product data                  |
|-------------------------------------|------------------------------------|-------------------------------|
| <b>Construction characteristics</b> |                                    |                               |
| Structure                           | ISO 2424                           | Woven loop pile               |
| Pile material                       | DIR 96/73, 96/74                   | 100% polyamide                |
| Fibre                               | Brand owner's                      |                               |
| Coloration                          | -                                  | Continuous dyed               |
| Backing                             | eTL                                | WT - Woven textile            |
| Dimensions                          | CEN/TS 14159                       | Approx. 400 cm                |
| Total thickness                     | ISO 1765                           | Apr 4,0 mm.                   |
|                                     | .                                  | 0.16"                         |
| Total carpet weight                 | ISO 8543                           | Apr 2.425 g/m2                |
|                                     | .                                  | 76.7 oz./yd2                  |
| Pile yarn weight                    | eTL                                | 700 g/m2                      |
|                                     | .                                  | 20.65 oz./yd2                 |
| <b>Performance characteristics</b>  |                                    |                               |
| Performance areas                   | EN 15114                           | Class 33 - Commercial - Heavy |
| Guarantee                           | eTL                                | Contract certificate          |
| Performance areas                   | Gulvbranchen                       | Class 33                      |
| Castor chair suitability            | EN 985                             | Intensive use                 |
| Suitability for use on stairs       | EN 1963                            | Yes                           |
| Static control                      | eTL                                | Permanently antistatic        |
| Body walking test                   | ISO 6356                           | Antistatic                    |
| Acou.insu. from impact noise        | ISO 717-2                          | 17 dB                         |
| Acoustical absorption               | ISO 354                            | 0,15 aW                       |
|                                     | Sound absorbtion class             | E                             |
| Suitability underfloorheating       | eTL                                | Apr 0,07 m2K/W                |
| Light reflectance                   | eTL                                | Testreport                    |
| Colour fastness to light            | ISO 105-B02                        | >5                            |
|                                     | AATCC 16                           | 5.0                           |
| Colour fastness to rubbing wet      | ISO 105-X12                        | >3                            |
|                                     | AATCC 165                          | 5.0                           |
| Colour fastness to rubbing dry      | ISO 105-X12                        | >3-4                          |
|                                     | AATCC 165                          | 5.0                           |
| Colour fastness to water plain      | ISO 105-E01                        | >3-4                          |
| Cleaning                            | AATCC 138                          | 5.0                           |
| Colour fast.Oxides of nitrogen      | AATCC 164                          | 4.5                           |
| Other performance tests             | ASTM D5252 Hexapod                 | 5.0/ 5.0                      |
|                                     | AATCC 134 Electrostatic propensity | 1.9 kV                        |
| <b>Safety &amp; Environment</b>     |                                    |                               |
| Fire classification                 | VKF/AEAI                           | Approved                      |
|                                     | ASTM E-648                         | Class 1                       |
|                                     | ASTM E662 Smoke Density            | <450                          |
|                                     | ASTM D2859 Surface Flamm.          | Pass                          |
|                                     | EN 13501-1 Euroclass               | Cfl-s1                        |
|                                     | ASISO 9239.1-2003                  | 4,70 KW/m2                    |
| CE Labeling                         | EN 14041                           | Certified                     |
|                                     | CPR                                | 1021-CPR-006-2/16             |

| Product description | Methods                        | Product data             |
|---------------------|--------------------------------|--------------------------|
| Indoor climate      | Declaration of Performance     | DOP 1C-PA-WT             |
|                     | Notified body no.              | 1021                     |
|                     | Ce Year                        | 07                       |
|                     | Content of PCP EN 12673        | DL                       |
|                     | Formaldehyde emission          | NA                       |
|                     | Slip resistance EN 13893       | Class DS                 |
|                     | M1                             | With WTA Backing         |
|                     | BASTA                          | Registered               |
|                     | Green Label Plus               | Approved                 |
|                     | Emissions dans l'air intérieur | A+/A+                    |
| Environment         | Indoor Air Comfort Gold        | Group 14                 |
|                     | ABG                            | ABG-28-02-14-01-2018     |
|                     | Byggardeklaration              | With WTA Backing         |
|                     | BREEAM-NOR                     | With WTA Backing         |
|                     | Environmental Product Decl.    | EPD-EGE-20130067-CBD1-EN |
|                     | Cradle To Cradle Certified     | Bronze certified         |
|                     | LEED                           | Qualified                |

### Guides

|                               |    |          |
|-------------------------------|----|----------|
| Installation + adhesive guide | DK | Dansk    |
|                               | N  | Norsk    |
|                               | S  | Svensk   |
|                               | GB | English  |
|                               | D  | Deutsch  |
|                               | F  | Francais |
| Cleaning, stain removal       | DK | Dansk    |
|                               | N  | Norsk    |
|                               | S  | Svensk   |
|                               | GB | English  |
|                               | D  | Deutsch  |
|                               | F  | Francais |

### Manufacturer characteristics

|                       |           |                               |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001  | Audited and verified by BVC   |
|                       | ISO 14001 | Audited and verified by BVC   |
|                       | EMAS      | Audited and verified by BVC   |
|                       | DS/OHSAS  | Audited and verified by BVC   |
|                       | DS 49001  | Audited and verified by BVC   |
|                       | CRuk      | Member of Carpet Recycling UK |



THE URGE TO EXPLORE SPACE