

# Epoca Compact

## Product Description



**ege**

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
<b>Construction characteristics</b>		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% polyamide
Fibre	Brand owner's	
Coloration	-	Continuous dyed
Backing	eTL	WT - Woven textile
Dimensions	CEN/TS 14159	Approx. 400 cm
Total thickness	ISO 1765	Apr 4,0 mm.
	.	0.16"
Total carpet weight	ISO 8543	Apr 2.425 g/m2
	.	76.7 oz./yd2
Pile yarn weight	eTL	700 g/m2
	.	20.65 oz./yd2
<b>Performance characteristics</b>		
Performance areas	EN 15114	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	ISO 717-2	17 dB
Acoustical absorption	ISO 354	0,15 aW
	Sound absorbtion class	E
Suitability underfloorheating	eTL	Apr 0,07 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colour fastness to water plain	ISO 105-E01	>3-4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	4.5
Other performance tests	ASTM D5252 Hexapod	5.0/ 5.0
	AATCC 134 Electrostatic propensity	1.9 kV
<b>Safety &amp; Environment</b>		
Fire classification	VKF/AEAI	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1
	ASISO 9239.1-2003	4,70 KW/m2
CE Labeling	EN 14041	Certified
	CPR	1021-CPR-006-2/16

Product description	Methods	Product data
Indoor climate	Declaration of Performance	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	07
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
	M1	With WTA Backing
	BASTA	Registered
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
Environment	GECA	Approved
	Indoor Air Comfort Gold	Group 14
	ABG	ABG-28-02-14-01-2018
	Byggvarudeklaration	With WTA Backing
	BREEAM-NOR	With WTA Backing
	Environmental Product Decl.	EPD-EGE-20130067-CBD1-EN
	Cradle To Cradle Certified	Bronze certified
	LEED	Qualified

### Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE