

Epoca Moss

Product Description



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 11,5 mm. 0.45"
Surface pile thickness	ISO 1766	Apr 9,0 mm.
Tufts	ISO 1763	Apr 140.900 pr.m2
Total carpet weight	ISO 8543	Apr 2.925 g/m2 103.3 oz./yd2
Pile yarn weight	eTL	1.750 g/m2 51.63 oz./yd2
Surface pile density	ISO 8543.	Apr 0,150 g/cm3

Performance characteristics

Performance areas	EN 1307	Class 31 Commercial - Moderate
Guarantee	eTL	Contract certificate
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
	EN 1815	Antistatic
Acou.insu. from impact noise	eTL	30 dB
Acoustical absorption	eTL	0,25 aW
Suitability underfloorheating	eTL	Apr 0,20 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	ISO 105-X12	>3
Colour fastness to rubbing dry	ISO 105-X12	>3-4
Colourfast. to water patterned	ISO 105-E01	>4

Safety & Environment

Fire classification	ASTM E-648	Class 1	
	ASTM E662 Smoke Density	<450	
	ASTM D2859 Surface Flamm.	Pass	
	EN 13501-1 Euroclass	Cfl-s1	
CE Labeling	EN 14041	Certified	
	CPR	1021-CPR-006-2/16	
	Declaration of Performance	DOP 1C-PA-WT	
	Notified body no.	1021	
	Ce Year	18	
	Content of PCP EN 12673	DL	
	Formaldehyde emission	NA	
	Slip resistance EN 13893	Class DS	
	Indoor climate	Emissions dans l'air intérieur	A+/A+
		Indoor Air Comfort Gold	Group 7
	ABG	ABG-28-02-07-02-2018	

Product description	Methods	Product data
Environment	Recycled Content, ISO 14021	Apr 4,5 %
	Recycled Content for LEED	Apr 4,5 %

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

ege

THE URGE TO EXPLORE SPACE