

Epoca Moss

Product Description



ege

THE URGE TO EXPLORE SPACE

| Product description | Methods | Product data |
|-------------------------------------|------------------|---------------------------------|
| Construction characteristics | | |
| Structure | ISO 2424 | Tufted cut pile |
| Gauge | ISO 2424 | 1/8 |
| Pile material | DIR 96/73, 96/74 | 100% polyamide |
| Coloration | - | Continuous dyed |
| Backing | eTL | WT - Woven textile |
| Dimensions | ISO 3018 | Approx. 400 cm |
| Total thickness | ISO 1765 | Apr 11,5 mm. 0.45" |
| Surface pile thickness | ISO 1766 | Apr 9,0 mm. |
| Tufts | ISO 1763 | Apr 140.900 pr.m2 |
| Total carpet weight | ISO 8543 | Apr 2.925 g/m2 103.3 oz./yd2 |
| Pile yarn weight | eTL | 1.750 g/m2 51.63 oz./yd2 |
| Surface pile density | ISO 8543. | Apr 0,150 g/cm3 |

Performance characteristics

| | | |
|--------------------------------|-------------|-----------------------------------|
| Performance areas | EN 1307 | Class 31 Commercial - Moderate |
| Guarantee | eTL | Contract certificate |
| Static control | eTL | Permanently antistatic |
| Body walking test | ISO 6356 | Antistatic |
| | EN 1815 | Antistatic |
| Acou.insu. from impact noise | eTL | 30 dB |
| Acoustical absorption | eTL | 0,25 aW |
| Suitability underfloorheating | eTL | Apr 0,20 m2K/W |
| Light reflectance | eTL | Testreport |
| Colour fastness to light | ISO 105-B02 | >5 |
| Colour fastness to rubbing wet | ISO 105-X12 | >3 |
| Colour fastness to rubbing dry | ISO 105-X12 | >3-4 |
| Colourfast. to water patterned | ISO 105-E01 | >4 |

Safety & Environment

| | | | |
|---------------------|----------------------------|--------------------------------|---------|
| Fire classification | ASTM E-648 | Class 1 | |
| | ASTM E662 Smoke Density | <450 | |
| | ASTM D2859 Surface Flamm. | Pass | |
| | EN 13501-1 Euroclass | Cfl-s1 | |
| CE Labeling | EN 14041 | Certified | |
| | CPR | 1021-CPR-006-2/16 | |
| | Declaration of Performance | DOP 1C-PA-WT | |
| | Notified body no. | 1021 | |
| | Ce Year | 18 | |
| | Content of PCP EN 12673 | DL | |
| | Formaldehyde emission | NA | |
| | Slip resistance EN 13893 | Class DS | |
| | Indoor climate | Emissions dans l'air intérieur | A+/A+ |
| | | Indoor Air Comfort Gold | Group 7 |
| | ABG | ABG-28-02-07-02-2018 | |

| Product description | Methods | Product data |
|---------------------|-----------------------------|--------------|
| Environment | Recycled Content, ISO 14021 | Apr 4,5 % |
| | Recycled Content for LEED | Apr 4,5 % |

Guides

| | | |
|-------------------------------|----|----------|
| Installation + adhesive guide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| Cleaning, stain removal | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer characteristics

| | | |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | DS/OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |

ege

THE URGE TO EXPLORE SPACE