

Highline 1100 on WT - Woven textile

Product Description



ege

THE URGE TO EXPLORE SPACE

| Product description | Methods | Product data |
|-------------------------------------|------------------|--------------------------------|
| Construction characteristics | | |
| Structure | ISO 2424 | Tufted cut pile |
| Gauge | ISO 2424 | 1/8 |
| Pile material | DIR 96/73, 96/74 | 100% regenerated Econyl PA6 |
| Coloration | - | Millitron dyed |
| Backing | eTL | WT - Woven textile |
| Dimensions | ISO 3018 | Approx. 400 cm |
| Total thickness | ISO 1765 | Apr 8,0 mm. 0.32" |
| Surface pile thickness | ISO 1766 | Apr 5,5 mm. |
| Tufts | ISO 1763 | Apr 197.100 pr.m2 |
| Total carpet weight | ISO 8543 | Apr 2.550 g/m2 75.2 oz./yd2 |
| Pile yarn weight | eTL | 1.100 g/m2 32.45 oz./yd2 |
| Surface pile density | ISO 8543. | Apr 0,155 g/cm3 |

Performance characteristics

| | | |
|--------------------------------|------------------------------------|-------------------------------|
| Performance areas | EN 1307 | Class 33 - Commercial - Heavy |
| Guarantee | eTL | Contract certificate |
| Performance areas | Gulvbranchen | Class 33 |
| Castor chair suitability | EN 985 | Intensive use |
| Suitability for use on stairs | EN 1963 | Yes |
| Static control | eTL | Permanently antistatic |
| Body walking test | EN 1815 | Antistatic |
| Acou.insu. from impact noise | ISO 717-2 | 27 dB |
| Acoustical absorption | ISO 354 | 0,20 aW |
| Suitability underfloorheating | eTL | Apr 0,14 m2K/W |
| Light reflectance | eTL | Testreport |
| Colour fastness to light | ISO 105-B02 | >5 |
| | AATCC 16 | 5.0 |
| Colour fastness to rubbing wet | ISO 105-X12 | >3 |
| | AATCC 165 | 5.0 |
| Colour fastness to rubbing dry | ISO 105-X12 | >3-4 |
| | AATCC 165 | 5.0 |
| Colourfast. to water patterned | ISO 105-E01 | >4 |
| Cleaning | AATCC 138 | 5.0 |
| Colour fast.Oxides of nitrogen | AATCC 164 | 5.0 |
| Other performance tests | Golf Spike Resistance Test | 3,2 |
| | ASTM D5252 Hexapod | 4.0/ 4.0 |
| | - | Commercial - Heavy |
| | AATCC 134 Electrostatic propensity | 3.1 kV |

Safety & Environment

| | | |
|---------------------|-------------------------|----------|
| Fire classification | VKF/AEAI | Approved |
| | BS 6853, NF X 70-100 | Approved |
| | ASTM E-648 | Class 1 |
| | ASTM E662 Smoke Density | <450 |

| Product description | Methods | Product data |
|-----------------------------|--------------------------------|-------------------------|
| CE Labeling | ASTM D2859 Surface Flamm. | Pass |
| | CAN,ULC-S102.2 | FSC1 66 |
| | Polen std. | OK |
| | EN 13501-1 Euroclass | Cfl-s1 |
| | HU,MSZ 14800-9:1985 | Suitable |
| | China | Cfl-s1,t0 |
| | EN 14041 | Certified |
| | CPR | 1021-CPR-006-2/16 |
| | Declaration of Performance | DOP 1C-PA-WT |
| | Notified body no. | 1021 |
| | Ce Year | 07 |
| | Content of PCP EN 12673 | DL |
| | Formaldehyde emission | NA |
| Indoor climate | Slip resistance EN 13893 | Class DS |
| | M1 | With WTA Backing |
| | INSTA 800 | Dust level 5 |
| | BASTA | Registered |
| | Green Label Plus | Approved |
| | Green Label Singapore | Approved |
| | Emissions dans l'air intérieur | A+/A+ |
| | Indoor Air Comfort Gold | Group 3 |
| | ABG | ABG-28-01-03-01-2018 |
| | Environment | BRE |
| Byggardeklaration | | eBVD |
| Environmental Product Decl. | | EPD-EGE-2013103-CBC1-EN |
| Cradle To Cradle Certified | | Bronze certified |
| Recycled Content, ISO 14021 | | Apr 42,0 % |
| Recycled Content for LEED | | Apr 32,0 % |
| LEED | | Qualified |

Guides

| | | |
|-------------------------------|----|----------|
| Installation + adhesive guide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| Cleaning, stain removal | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer characteristics

| | | |
|-----------------------|-----------|-----------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |



THE URGE TO EXPLORE SPACE

| Product description | Methods | Product data |
|----------------------------|----------------|----------------------------------|
| | DS/OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |

ege

THE URGE TO EXPLORE SPACE