

Highline 1100 on WT - Woven textile

Product Description



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	ETL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 8,0 mm. 0.32"
Surface pile thickness	ISO 1766	Apr 5,5 mm.
Tufts	ISO 1763	Apr 197.100 pr.m2
Total carpet weight	ISO 8543	Apr 2.550 g/m2 75.2 oz./yd2
Pile yarn weight	ETL	1.100 g/m2 32.45 oz./yd2
Surface pile density	ISO 8543.	Apr 0,155 g/cm3

Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	ETL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	ETL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	ISO 717-2	27 dB
Acoustical absorption	ISO 354	0,20 aW
Suitability underfloorheating	ETL	Apr 0,14 m2K/W
Light reflectance	ETL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	4.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Other performance tests	Golf Spike Resistance Test	3,2
	ASTM D5252 Hexapod	4.0/ 4.0
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	3.1 kV

Safety & Environment

Fire classification	VKF/AEAI	Approved
	BS 6853, NF X 70-100	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450

Product description	Methods	Product data
CE Labeling	ASTM D2859 Surface Flamm.	Pass
	CAN,ULC-S102.2	FSC1 66
	Polen std.	OK
	EN 13501-1 Euroclass	Cfl-s1
	HU,MSZ 14800-9:1985	Suitable
	China	Cfl-s1,t0
	EN 14041	Certified
	CPR	1021-CPR-006-2/16
	Declaration of Performance	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	07
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
Indoor climate	Slip resistance EN 13893	Class DS
	M1	With WTA Backing
	INSTA 800	Dust level 5
	BASTA	Registered
	Green Label Plus	Approved
	Green Label Singapore	Approved
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 3
	ABG	ABG-28-01-03-01-2018
	Environment	BRE
Byggvarudeklaration		eBVD
Environmental Product Decl.		EPD-EGE-2013103-CBC1-EN
Cradle To Cradle Certified		Bronze certified
Recycled Content, ISO 14021		Apr 42,0 %
Recycled Content for LEED		Apr 32,0 %
LEED		Qualified

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC

ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
	DS 49001 CRuk	Audited and verified by BVC Member of Carpet Recycling UK

ege

THE URGE TO EXPLORE SPACE