

# ReForm Calico Broadloom

## Product Description



**ege**

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
<b>Construction characteristics</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 7,0 mm. 0.28"
Surface pile thickness	ISO 1766	Apr 4,0 mm.
Tufts	ISO 1763	Apr 153.000 pr.m2
Total carpet weight	ISO 8543	Apr 2.200 g/m2 64.9 oz./yd2
Pile yarn weight	eTL	680 g/m2 20.06 oz./yd2
Surface pile density	ISO 8543.	Apr 0,115 g/cm3

### Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	ISO 717-2	24 dB
Acoustical absorption	ISO 354	0,20 aW
	Sound absorbtion class	E
Suitability underfloorheating	eTL	Apr 0,12 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	3.5
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Other performance tests	ASTM D5252 Hexapod	3.5/3.0
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	0.6 kV

### Safety & Environment

Fire classification	VKF/AEAI	Approved
	BS 6853, NF X 70-100	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450

Product description	Methods	Product data	
CE Labeling	ASTM D2859 Surface Flamm.	Pass	
	EN 13501-1 Euroclass	Cfl-s1	
	HU,MSZ 14800-9:1985	Suitable	
	ASISO 9239.1-2003	10,20 KW/m2	
	EN 14041	Certified	
	CPR	1021-CPR-006-2/16	
	Declaration of Performance	DOP 1C-PA-WT	
	Notified body no.	1021	
	Ce Year	07	
	Content of PCP EN 12673	DL	
	Formaldehyde emission	NA	
	Slip resistance EN 13893	Class DS	
	Indoor climate	INSTA 800	Dust level 5
		BASTA	Registered
Green Label Plus		Approved	
Green Label Singapore		Approved	
Emissions dans l'air intérieur		A+/A+	
Indoor Air Comfort Gold		Group 3	
ABG		ABG-28-01-03-01-2018	
Environment	Environmental Product Decl.	EPD-EGE-20150030-CBC1-EN	
	Cradle To Cradle Certified	Bronze certified	
	LEED	Qualified	

## Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

## Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE