

Soft Dreams Lux any shape

Product Description



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	ETL	CF - Comfort felt
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 16,0 mm.
Tufts	ISO 1763	Apr 48.000 pr.m2
Total carpet weight	ISO 8543	Apr 3.650 g/m2
Pile yarn weight	ETL	2.200 g/m2
Surface pile density	ISO 8543.	Apr 0,150 g/cm3
Performance characteristics		
Performance areas	ETL	22 - Domestic - General/Medium
Guarantee	ETL	Wear guarantee 5 Years
Static control	ETL	Permanently antistatic
Suitability underfloorheating	ETL	Yes
	ISO 8302	Yes
Safety & Environment		
Fire classification	EN 14041	Efl
CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP E
	Notified body no.	NA
	Ce Year	17
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
Guides		
Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Manufacturer characteristics		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
		UK



THE URGE TO EXPLORE SPACE